





COMMERCIAL AND ARCHITECTURAL  
DOOR MANUFACTURER

U.S.A. : 1 800 363.2248  
Can. : 1 800 463.3124  
sales@lambtondoors.com

## COMMERCIAL AND ARCHITECTURAL DOORS

### Particleboard core

Blind edge **5-8300-BE**



#### SPECIFICATIONS

#### DESCRIPTION

<b>Type</b>	Particleboard core (interior use).
<b>In conformity with industry standards</b>	ARCHITECTURAL WOODWORK STANDARDS-ED.1 W.D.M.A. SERIES I.S.1-A-2004 CSA 0132.2 SERIES 90 ASTM D5456-09 ANSI A208.1
<b>Thickness</b>	1-3/4" (44 mm).
<b>Maximum size</b>	48" x 120" (1 219 mm x 3 048 mm).
<b>Stiles</b>	7/16" (11 mm) hardwood laminated to 4" (102 mm) structural composite lumber (SCL).
<b>Rails</b>	3" (76 mm) structural composite lumber (SCL).
<b>Core</b>	Particleboard core with a density of 28-32 PCF (449-513 kg/m <sup>3</sup> ) LD-1, bonded to the stiles and rails.
<b>Adhesive</b>	Type I (waterproof); PVA (no urea formaldehyde); <b>VOC&lt;0.683 g/L.</b>
<b>Face</b>	Wood veneer bonded to a composite crossband.
<b>Options</b>	<ul style="list-style-type: none"> <li>● LD-2 core available.</li> <li>● 20 minute rating neutral or positive pressure.</li> </ul> Refer to Fire Door Section of our website for details.
<b>Lite and louver opening</b>	Wood louvers not permitted in 20 minute labeled doors. Minimum 5" (127 mm) from stiles or rails. Minimum 1-1/2" (38 mm) from cut-out to cut-out. Refer to Option Section of our website for details.
<b>Notes</b>	Stile and rail dimensions shown are rough sizes, before trimming. Dimensions will vary due to prefit requirements.
<b>Warranty</b>	Life of original installation. See our complete warranty for details.
<b>Factory Finish</b>	UV Finishing System. Stain, clearcoat, finish available. Custom color matching available. Seal top and bottom standard. <b>NO VOC.</b>
<b>Environmental Description</b>	Recycled content (LEED MRc4.1, 4.2).



#### INFORMATION

[WWW.LAMBTONDOORS.COM](http://WWW.LAMBTONDOORS.COM)